

## **AROMEX 3000**

### **Product Description**

AROMEX 3000 is the distillate aromatic extract (DAE) with the very high aromatic contents and medium viscosity at high temperature which is obtained as the by product from solvent extraction process. It provide the good solvency and processability in manufacturing process. It can be used as the one component in a wide variety of finish products and operations such as rubber compounds and asphalt.

#### **Benefits**

- Medium viscosity at high temperature
- Good solvency
- Good processability in manufacturing process

#### **Applications**

 Can be used as the one component in a wide variety of finish products and operations such as rubber compounds and asphalt

The Moving Innovation



# **AROMEX 3000**

Typical Characteristics			
Tests	Methods	Units	Results
Density at 15 °C	ASTM D4052-11	g/ml	0.9932
Kinematic Viscosity at 100 °C	ASTM D445-11	mm²/s	29.92
Flash Point (COC)	ASTM D92-16	°C	284
Pour Point	ASTM D97	°C	16
Aniline Point	ASTM D611-12	°C	40
Total Sulfur Content	ASTM D4294	%wt.	3.63
Carbon Type Analysis			
%CA	ASTM D2140-08	%	45
%CN	ASTM D2140-08	%	30
%CP	ASTM D2140-08	%	25

The above mentioned data are only indication and do not present any guarantee. Any deviations of the data are no reason for claim.

### **Health and Safety**

This product shows no significant health or safety hazard when used under the recommended applications and suitable handling.

Avoid the direct contact. Wash immediately after contact. Health and safety information is available on the Safety Data Sheet (SDS) which can be obtained from http://pttlubricants.pttor.com



Note: Data and information contained in this publication are based on standard test under laboratory conditions and/or performance test. To consider the use of PTT Lubricants' products in particular application, customer is responsible for determining whether product and information are appropriate for customer conditions or should consult with PTT Lubricants' technical service division. The procedure of using any lubricant may differ or change depended on different machines and their manuals. Therefore, we recommend to read, understand and review the latest SDS in order to ensure the use of product is accomplished safety.

